

Contents

Foreword	7
List of most frequently used symbols	9
1. Instability of homogeneous plastic strain and localized necking of thin sheets and shear band growth in three-dimensional bodies. Basic considerations for incompressible materials with pressure independent yield surface	14
1.1. Relation between strain localization and fracture initiation	14
1.2. Localized necking as a two-dimensional problem	15
1.3. Stability and instability of homogeneous strain in three-dimensional bodies	18
1.4. Strain localization in bands	20
2. Three-dimensional constitutive equations of incompressible materials	22
2.1. Classic constitutive equations based on plastic flow theory, with isotropic expansion of yield surface	22
2.2. Constitutive equations of deformation theory as a model of polycrystalline materials behaviour at small deviations from the proportional loading	23
2.3. Constitutive equations with more complex properties under generally non-proportional loading	25
3. Constitutive equations of void-containing materials based on the plastic flow theory	27
3.1. Yield surface and deduction of the differential form of constitutive equations	27
3.2. Determination of material parameters in Gurson–Tvergaard equations	32
3.3. Nucleation of voids	33
4. Constitutive equations of void-containing polycrystalline materials	34
4.1. Physical mechanisms promoting strain localization	34
4.2. Constitutive equations permitting to model superposition of effects of both principal mechanisms	35
5. Localized necking of thin sheets of incompressible materials for different strain geometries	40
5.1. Isotropic material	40
5.2. Anisotropy – simple model with quadratic yield surface	43
5.3. Non-conventional yield surface models	47
5.4. Influence of inhomogeneities on localized necking of thin sheets	50
6. Shear band formation in three-dimensional bodies for different strain geometries	52
6.1. Materials with volume dilatation	52
6.2. Incompressible materials with pressure independent yield surface	55
7. Influence of inhomogeneities of different types on shear band initiation at plane deformation of incompressible material	59
7.1. Inhomogeneities in a form of bands	60

7.2. Inhomogeneities bounded in plane section	67
7.3. General conclusions valid for both idealized geometries of inhomogeneities	71
8. Applications – comparison of theory and experiments	73
8.1. Interpretation of morphology of ductile fracture and of sequence of processes leading to ductile fracture	73
8.2. Prediction of ductile fracture of polycrystalline materials in form of thin sheets ...	74
8.3. Prediction of ductile fracture of polycrystalline materials in form of three-dimensional bodies	76
8.3.1. Incompressible materials with pressure independent yield surface	76
8.3.2. Void-containing materials	79
9. Correlation of constitutive properties and fracture toughness and simulation of crack growth resistance curves	88
9.1. Principal knowledge obtained from calculations by the finite element method	88
9.2. Simple correlations of conventional characteristics of tensile properties and fracture toughness	90
9.3. Constitutive equations involving gradient of strain and characteristic size of the process zone at the crack tip	92
9.4. Correlation of constitutive properties and fracture toughness based on analysis of strain localization in bands	96
9.5. Simulation of crack growth resistance curves based on both constitutive properties and local fracture criteria	100
10. Conclusions and perspectives	105
10.1. Constitutive equations development	105
10.2. Bifurcation analysis for homogeneous strain rate insensitive materials and ductile fracture prediction	105
10.3. Inhomogeneities and strain rate sensitivity of stress in relation to the ductile fracture prediction	106
10.4. Relation of constitutive properties and parameters of fracture mechanics	106
References	108
Český souhrn	112
Index	115