## CONTENTS

|   | CONTENTS   | 3   |
|---|--|---|
| 1.  | OVERVIEW   | 5   |
| 1.1   | Role of Mechanics of Materials and Solid Mechanics in Design   | 5   |
| 2   | SIMPLE STRESS AND STRAIN   | 6   |
| 2.11<br>2.12<br>2.13                          | Load Direct or normal stress ( $\sigma$ ) Direct strain ( $\varepsilon$ ) Sign convention for direct stress and strain Elastic materials - Hooke's law Modulus of elasticity - Young's modulus Tensile test Ductile materials Brittle materials Brittle materials Poisson's ratio Application of Poisson's ratio to a two-dimensional stress system Shear stress Shear strain. Modulus of rigidity Allowable working stress-factor of safety | 7<br>7<br>7<br>8<br>8<br>8<br>9<br>12<br>12<br>13<br>14<br>15<br>15 |
| 3   | SHEARING FORCE AND BENDING MOMENT DIAGRAMS   | 17  |
| 3.1<br>3.2<br>3.3<br>3.4<br>3.5<br>3.6<br>3.7 | Summary Shearing force (S.F) and bending moment (B.M) Shearing force sign convention Bending moment sign convention S.F. and B.M. diagrams for beams carrying concentrated loads only S.F. and B.M. diagrams for uniformly distributed loads Relationship between S.F., B.M. and intensity of loading q  | 17<br>17<br>17<br>18<br>19<br>21<br>22                              |
| 4   | BENDING  | 25  |
| 4.1<br>4.2<br>4.3<br>4.4<br>4.5<br>4.6        | Summary Introduction Simple bending theory Neutral axis Section modulus Second moment of area  | 25<br>26<br>26<br>29<br>30<br>31                                    |
| 5   | SLOPE AND DEFLECTION OF BEAMS  | 33  |
| 5.1<br>5.2                                    | Summary<br>Introduction  | 33<br>33  |

## Lenert,J.: Strength of Materials: CONTENES

| 5.3        | Relationship between loading, S.F., B.M., slope and deflection   | 34 |
|------------|--|----|
| 5.4        | Direct integration method  | 35 |
| 5.5        | Principle of superposition   | 36 |
| 5.6        | Energy method  | 36 |
| 5.7        | Maxwell's theorem of reciprocal displacements  | 36 |
| 6          | TORSION  | 38 |
| 6.1        | Summary  | 38 |
| 6.2        | Simple torsion theory  | 39 |
| 6.3        | Angle of twist   | 39 |
| 6.4        | Shear stresses   | 40 |
| 6.5        | Polar second moment of area  | 41 |
| 6.6        | Shear stress and shear strain in shafts  | 41 |
| 6.7        | Section modulus  | 42 |
| 6.8        | Torsional rigidity   | 43 |
| 6.9        | Torsion of hollow shafts   | 43 |
| 6.10       | Composite shafts-series connection   | 43 |
| 6.11       | Composite shafts-parallel connection   | 44 |
| 7          | THEORIES OF ELASTIC FAILURE  | 46 |
| 7.1        | Ç  | 46 |
| 7.1<br>7.2 | Summary<br>Introduction  | 46 |
| 7.3        | Maximum principal stress theory  | 40 |
| 7.4        | Maximum shear stress theory  | 48 |
| 7.5        | Maximum principal strain theory  | 48 |
| 7.6        | Maximum total strain energy per unit volume theory   | 48 |
| 7.7        | Maximum shear strain energy per unit volume (or distortion energy) theory                                      | 49 |
| 7.8        | Mohr's modified shear stress theory for brittle materials (sometimes referred to as                            |    |
|            | the internal friction theory)  | 49 |
| 7.9        | Graphical representation of failure theories for two-dimensional stress systems (one principal stress is zero) | 51 |
|            |  |    |
| 7.10       | Brittle materials  | 57 |
|            | Limitations of the failure theories  | 57 |
|            | Effect of stress concentrations  | 58 |
| 7.13       | Safety factors   | 58 |
| 8          | APPENDIX   | 61 |
| 8.1        | Solution of the supported beam via FEM software ANSYS  | 61 |
| 8.2        | Printout of the program (for ANSYS software)   | 61 |
|            | REFERENCES   | 63 |
|            | was the control of the first the many areas of Mechanics of Managian. Actions these are                        |    |